



TUNNEL	Ricopertura Enrobing Enrobage	Decorazione Decoration Décoration	Lunghezza tunnel Tunnel lenght Longeur tunnel	Coda Tail Queue	Distaccatore Detachment Détacheur	Totale Total Total
5 m	1100	400	5000	400	400	7300
		600			600	7700
		800			800	8100
		1000			1000	8500
		1200			1200	8900
6 m	1100	400	6000	400	400	8300
		600			600	8700
		800			800	9100
		1000			1000	9500
		1200			1200	9900
8 m	1100	400	8000	400	400	10300
		600			600	10700
		800			800	11100
		1000			1000	11500
		1200			1200	11900
12 m	1100	400	12000	400	400	14300
		600			600	14700
		800			800	15100
		1000			1000	15500
		1200			1200	15900
16 m	1100	400	16000	400	400	18300
		600			600	18700
		800			800	19100
		1000			1000	19500
		1200			1200	19900



Tunnel 600 is designed to enrobe and cool various types of chocolate products. Built entirely in stainless steel, this tunnel is equipped with a 600mm wide belt and two separate refrigeration units which allow for the creation of zones of different temperatures. The temperature is set from a very user friendly and versatile control panel that allows the operator to easily navigate between the various functions of the machine. This machine is designed for industrial production.

The machine is available as standard in different lengths. However, the company is also able to manufacture it to any required custom length if this were to be requested.

Please note that with regards to the total dimensions, as well as the cooling chamber one also needs to take into consideration the decoration zone, which will have a length chosen by the customer, and the detacher.

The latter is an optional belt that is very useful in the enrobing procedure, since it facilitates and noticeably improves the quality of the final product.

Mechanical characteristics

Overall dimensions -
 Empty weight -
 Material in contact with food inox AISI 304 L
 Gaskets PTFE
 Tank capacity -

Cooling system characteristics

Cooling group [Fr/h] 7600 / 8000
 Refrigerant gas R448A
 Refrigerant gas quantity [g] 2800 x 2

Electrical characteristics

Total installed power [kW] from 8
 Supply voltage [VAC] 400 / 220
 Number of phases 3
 Frequency [Hz] 50 / 60
 Auxiliary voltage [Vdc] +24
 Enclosure degree of protection IP65
 Connection type: industrial plug 16A - 5 poles

